

## 2/1GN 1 SECTION COUNTER



### GENERAL FEATURES

- Ext & int 304 S/S ; Back and base galvanized
- Anti-condensation door mullion heaters
- Removable cassette type condensing unit and evaporator
- Forced air cooling system
- Hygienic one-piece S/S dished base with round corners
- Removable door gasket ; Digital smart controller
- Adjustable PE coated shelves; Accommodates with 2/1GN size
- Self-vaporizing system, no need drainage connect
- Environmental friendly refrigerant; CFC-free insulation
- High density insulation foam 43 kg/m<sup>3</sup>
- Integrated bending handle
- Less 90° self closing door, over 90° door opening
- Adjustable legs or castors (Optional)
- Cylindrical door locks
- Designed to operate up to 43 °C

| MODEL        |                   |             |           |             |           |             |
|--------------|-------------------|-------------|-----------|-------------|-----------|-------------|
|              | HCR2G1D           | LCR2G1D     | HCR2G1N   | LCR2G1N     | HCR2G1W   | LCR2G1W     |
| Temp(°C)     | +1 / +4°C         | -22 / -18°C | +1 / +4°C | -22 / -18°C | +1 / +4°C | -22 / -18°C |
| Dimension    | 1080x770x850      |             |           |             |           |             |
| Power (W)    | 770               | 880         | 770       | 880         | 770       | 880         |
| Voltage      | 220V / 50Hz / 1PH |             |           |             |           |             |
| Capacity (L) | 214               |             |           |             |           |             |
| Refrigerant  | R134a             | R404a       | R134a     | R404a       | R134a     | R404a       |
| Defrost      | Off cycle         | Electric    | Off cycle | Electric    | Off cycle | Electric    |

### Important Notes:

- \* All refrigeration equipment requires adequate ventilation for efficient performance.
- \* Kalo reserve the right to change product specifications stated without prior notice.